

LODE  KING

www.lodeking.com



AHV SUPER-B

GRAIN TRAILER

SPECIFICATIONS

BODY STRUCTURE

- LENGTH** Lead 28'6", Pull 30'5"
- EXTERIOR WIDTH** 102"
- INTERIOR WIDTH** 97.75"
- HEIGHT** 79", 82" and 85" wall height available
- STRUCTURE** Steel king pin section and suspension frame; walls of double skin aluminum with internal stiffeners, riveted construction
- SLOPES** Aluminum, 30 deg. except 43 deg. at rear of Lead
- HOPPERS** Aluminum, formed with two rows of stiffeners, chute frame riveted to hopper cone
- LADDERS** Aluminum, front and rear with interior access steps
- LANDING GEAR** .. Holland Mark V, 2 speed with attached handle
- FENDERS** NF166SS with closure plates
- MUDFLAPS** Heavy duty, black rubber, anti-sail
- TARP** Michel's with flip-stops, reinforcement over roof-bows, fiberglass ridge-pole
- TARP SUPPORTS** . Aluminum roof bows and end caps
- LIGHTING** 7-Way connector at front, LED lights, Lode-King sealed wiring system
- FINISH** Pre-painted aluminum exterior, natural aluminum hoppers and interior surfaces, painted steel king pin section and suspension frame

RUNNING GEAR

- SUSPENSION** Intraax AANT23K air ride
- AXLES** Hendrickson 5.75" round on Intraax. All axles 77.5" track
- ABS** Meritor Wabco
- OIL SEALS** Guardian HP
- HUBS** 10 stud, hub piloted, cast or lighter weight options
- DRUMS** Outboard, cast or lighter weight options
- BRAKES** 16 1/2" x 7" quick change
- BRAKE LININGS**.. Abex 931-162
- WHEELS** Aluminum 22.5" or 24.5"
- TIRES** Wide range of Michelin and Bridgestone products available

OPTIONS

- 4 in a row full coverage 102" wide mudflaps ahead of landing gear
- 3 in a row mudflaps ahead of second hopper
- Brake pot belting ahead of suspension
- Load gauge enclosure with internal light and a sealed window in the door
- Air outlet in load gauge enclosure
- Implement style loading light for each hopper
- Implement style unloading light
- Chute openings from both sides
- Vent in each hopper
- Aluminum fill plate in bumper with Lode-King logo
- Tow hooks at rear of pull
- Placard holders
- Hubodometer
- Lift Axles
- Extended service brake linings

TRAILER VOLUME (CUBIC FT.)

Wall Height	Lead 28'6"		Pull 30'5"		Total	
	WATER LEVEL	HEAPED	WATER LEVEL	HEAPED	WATER LEVEL	HEAPED
79"	1184	1281	1369	1473	2553	2754
82"	1238	1334	1427	1531	2665	2865
85"	1291	1388	1484	1588	2775	2976



LODE-KING INDUSTRIES

A Division of Triple E Canada Ltd.

Box 1146, 135 Canada Street
 Winkler, MB Canada R6W 4B2
 T (204) 325-4345 F (204) 325-5369
 www.lodeking.com



Product improvement is an ongoing process a Lode-King Industries. Thus we reserve the right to change any specifications or components on any specifications or components on any or all products without prior notice; errors or omissions excepted. Lode-King Industries is under no obligation to undertake modifications to units manufactured prior to changes in specifications. Printed in Canada.

Distributed By: